



Customer:
Project:
Product:

Powder coatings are organic coatings which must be regularly cleaned and maintained in to ensure the decorative and protective properties of the coating are retained. Records of all cleaning schedules and frequencies shall be kept and maintained by Customer according to the process outlined below and shall be available to GRECO upon request.

Cleaning Method

1. Usual maintenance of Products must adhere to the following steps:
 - a. Clean using an appropriate cleaning product, as defined below
 - b. Clear water rinsing
 - c. Wiping with a soft cloth
2. All surfaces shall be cleaned using a soft cloth or sponge, and no cloth shall be harsher than natural bristle brushes.
3. If the Product is subject to any hazardous and unusual environmental factors or is located within one (1) mile of the seashore, an estuary or marine environments, GRECO must be consulted on an individual project basis for best maintenance practices.

Cleaning Products

1. Before cleaning, Customer must consult and adhere to the underlying instructions contained within the Product Data Sheet as attached in Exhibit B.
2. Usual maintenance cleaning may be done using water with a mild detergent (pH 5 to 8).
3. If atmospheric pollution has resulted in heavy soiling of the Coating, some stains or marks may require stronger domestic products, such as alcohol, petroleum spirits, white spirits or bleach diluted to five percent (5%). In this instance, Customer must rinse the Coating immediately after using the cleaning product.
4. In no circumstance shall any abrasive cleaner, polish, cleanings containing keytones or esters be used.

Frequency

Customer shall clean the Product according to the following frequencies:

1. Six (6) times per year for all Products located within one (1) mile of the seashore
 - a. The cleaning cycle shall commence within two (2) months of installation
 - b. Cleaning shall be conducted in intervals not to exceed two (2) months
 - c. Customer shall maintain fully documented records throughout the Warranty term
2. Four (4) times per year for all Products located more than one (1) mile of the seashore
 - a. The cleaning cycle shall commence within two (2) months of installation
 - b. Cleaning shall be conducted in intervals not to exceed two (2) months
 - c. Customer shall maintain fully documented records throughout the Warranty term

Additional Factors

1. Damage from installation, mechanical processes, jig marks and other related defects must be repaired immediately in order for the Warranty to remain in effect.
2. Protective tapes used in installation must be a "low tack" quality and must not be left in contact with the surface for more than one (1) month.
3. PPC must approve all sealants and mastics prior to installation in order to for Warranty to remain in effect.

CHLOR RID International, Inc.



P.O. Box 908 Chandler, AZ 85244
 Toll Free 800-422-3217 Office 480-821-0039 Fax 480-821-0364
www.chlor-rid.com

CHLOR*RID® LIQUID SOLUBLE SALT REMOVER DIRECTIONS

DESCRIPTION: CHLOR*RID is a unique functional performance product which aids in the removal of chlorides, sulfates, nitrates and other surface reacted soluble salts.

HIGH PRESSURE WASHING: CHLOR*RID is added to the water of the pressure washer, usually in a dilution ratio of 1:100. (See Testing below) Add CHLOR*RID by means of a metering pump or add to a reservoir water supply. A siphon device may be used, but most such devices lack dilution control and positive input. Use potable water or other approved source. A minimum 3000 p.s.i. pressure washer is recommended. A zero degree rotating nozzle is also recommended. Flush washer and lines prior to application. Can also be applied through UHP waterjetting equipment. Hold pressure nozzle perpendicular to the surface and preferably 4 to 8 inches away to ensure all surfaces are washed with direct high pressure. In areas of deep pitting, slow the wash speed to enable better cleaning. Do not rinse. Typical application rate is 300 to 1000 Sq. Ft. per gallon of CHLOR*RID.

HAND WASHING: Use CHLOR*RID DTS™ (Direct To Surface) according to directions. CHLOR*RID DTS is ready to use direct from the container- no dilution necessary.

WET ABRASIVE BLASTING: Add CHLOR*RID to the system at 1 U.S. gallon per 300-1000 square feet of surface to be blasted using potable water or other approved source. (Dilution ratio of 1:250 typical.) Add CHLOR*RID to rinse water at 1:250 ratio (or HOLD*BLAST in a 1:50 dilution ratio to prevent flash rusting). Always use appropriate safety equipment.

MIST/VAPOR BLASTING: Add CHLOR*RID in a 1:100 dilution to the water of the mist blaster. The same water solution may be used for wash down of particulate matter after blasting (or HOLD*BLAST in a 1:50 dilution ratio to prevent flash rusting).

TESTING: After cleaning or blasting a small sample area, test the surface with a CHLOR*TEST™ kit to verify cleanliness. Adjust speed of travel, standoff distance, pressure or dilution as necessary and retest to verify desired cleanliness level is attained. Abrasives and water used should be tested with CHLOR*TEST kits "A" and "W" respectively.

Due to a wide variety of surface conditions, work environments, weather conditions, etc., these directions are general and may require alterations to better suit individual conditions. Call CHLOR RID International Inc. for recommendations for a specific project. CHLOR RID International Inc. assumes no liability for use or misuse of the product inconsistent with its labeling.

WARRANTY: CHLOR RID International Inc. warrants this product to be identical in chemical and physical properties from batch to batch within the specification limits of the raw materials used in its manufacture.

SAFETY PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. Do not mix with other chemicals. See M.S.D.S. for full precautions before use. This product is intended for professional use only.



CHLOR RID International, Inc.

P.O. Box 908 Chandler, AZ 85244
Toll Free 800-422-3217 Office 480-821-0039 Fax 480-821-0364
www.chlor-rid.com

CHLOR*RID®

LIQUID SOLUBLE SALT REMOVER DATA SHEET

DESCRIPTION: CHLOR*RID is an organic bonding chemical blend which aids in the removal of chlorides, sulfates and surface reacted salts. Contains no volatile organic compounds (VOC's), and is biodegradable.

CHLOR*RID is recommended for use in a maintenance wash solution to reduce corrosion and as part of surface preparation prior to application of primers or coatings on a variety of surfaces, including ferrous and non-ferrous metals, concrete, and others.

SURFACE PREPARATION: Best surface preparation yields the best results. If hydrocarbons are present, they should be removed prior to salt removal. Barrier materials, such as rust or scale or delaminated coatings, should be removed prior to salt removal. Sufficient mechanical force, such as pressure washing, wet abrasive blast, dry blast, or hand power tooling may be utilized for barrier materials to be removed as part of surface preparation procedures.

APPLICATION: CHLOR*RID can be introduced and applied by a variety of means. See Directions for hand cleaning, pressure washing, UHP waterjetting wet abrasive, and vapor/mist blasting methods. Contact CHLOR RID International, Inc. for other methods or technical support.

Before and after cleaning a small sample area (usually 25 Sq. Ft.), test the surface for contamination. Adjust travel speed, pressure or dilution as necessary and retest to assure desired cleanliness level is achieved. It is not necessary to use the entire contents. Partially filled containers should be closed tightly.

EQUIPMENT CLEANUP: Flush with clean fresh water.

- | | |
|--|-----------------------------------|
| * Color: Blue | * Packaging: 1/5/55 U.S. Gallon |
| * Typical coverage: 300-1000 Sq. Ft./ Gal. | * Single Component |
| * No VOC's | * Shelf Life: 36 months |
| * pH 3.3 (+/- 0.2) | * Application Temperature: +32° F |
| * Keep from freezing – if frozen, thaw before use. * Non-Flammable | |

WARRANTY: CHLOR RID International Inc. warrants this product to be identical in chemical and physical properties from batch to batch within the specification limits of the raw materials used in their manufacture.

SAFETY PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. Do not mix with other chemicals. See M.S.D.S. for full precautions prior to use. This product is intended for professional use only.