



Date:  
Customer Name:  
Job Name / Location:

PRODUCT:

### **KYNAR FINISH CLEANING AND MAINTENANCE:**

- Maintenance and cleaning must be documented in accordance with Warranty specifications. Systematic maintenance program must be instituted to clean the surface periodically so as to prevent the accumulation of concentrated salt deposits in areas of high salt concentration such as areas adjacent to the seashore. In the event of failure, customer shall furnish proof of proper maintenance.

#### Cleaning Method

1. Usual maintenance of Products must adhere to the following steps:
  - a. Clean using an appropriate cleaning product, as defined below
  - b. Clear water rinsing
  - c. Wiping with a soft cloth
2. All surfaces shall be cleaned using a soft cloth or sponge, and no cloth shall be harsher than natural bristle brushes.
3. If the Product is subject to any hazardous and unusual environmental factors or is located within one (1) mile of the seashore, an estuary or marine environments, Greco Aluminum Railings must be consulted on an individual project basis for best maintenance practices.

#### Cleaning Products

1. Before cleaning, customer must consult the cleaning product's MSDS sheet. Most commercial cleaning products have a toll-free number to reach technical support, and it is suggested to contact the manufacturer listed to ensure product is safe for organic coatings.
2. Usual maintenance cleaning may be done using water with a mild detergent or mild soap.
3. If atmospheric pollution has resulted in heavy soiling of the Coating, some stains or marks may require stronger domestic products, such as alcohol, petroleum spirits, white spirits or bleach diluted to five percent (5%). In this instance, Customer must rinse the Coating immediately after using the cleaning product.
4. In no circumstance shall any abrasive cleaner, polish, cleanings containing keytones or esters be used.

## Cleaning Frequency

Customer shall clean the Product according to the following frequencies:

1. Six (6) times per year for all Products located within one (1) mile of the seashore
  - a. The cleaning cycle shall commence within two (2) months of installation
  - b. Cleaning shall be conducted in intervals not to exceed two (2) months
  - c. Customer shall maintain fully documented records throughout the Warranty term
2. Four (4) times per year for all Products located more than one (1) mile of the seashore
  - a. The cleaning cycle shall commence within two (2) months of installation
  - b. Cleaning shall be conducted in intervals not to exceed two (2) months
  - c. Customer shall maintain fully documented records throughout the Warranty term

**Maintenance and cleaning must be documented in accordance with warranty specifications. In the event of coating failure, customer shall furnish proof of proper maintenance.**

9410 Eden Avenue, Hudson, FL 34667

Phone: (727) 372-1100

Fax: (727) 372-1100